

MEEVO Threads

80 Thread needle 30/2

100% Polyester wrapped thread with a polyester filament core. It is a lubricated thread that allows an exceptional use in the most demanding applications. It has excellent resistance to abrasion, because is a corespun thread with polyester filament core.

This feature allows the use of finer thread sizes, achieving a better seam aspect, keeping the resistance.



Composition

Polyester-Cotton

Colour

White

Produced in EU

Ticket no.	80
NE	30
N° Cables	2
TEX	40
Twist / TPM	710
Average strength cN	2124
Average strength g	2166
Elongation % (average)	14,5
Needle Size (Guide) Singer	14-18
Needle Size (Guide) Metric	90-110

Fastness	Colours
Washing at 60 °C	Grade 4
Rub fastness	Grade 4
Water fastness	Grade 4
Iron	Grade 4
Artificial light	Grade 4
	Grey scale

PHYSICAL AND CHEMICAL PROPERTIES

Shrinkage	Less than 1% at 150°C
Thermal properties	Melts at 250-260°C, softens at 220-240°C
	Cotton: It may discolour if exposed too long to high temperatures
Organic acids	Unaffected
Inorganic acids	Resistant to most acids
Alkalis	Unaffected
Organic solvents	Generally unaffected but soluble in some phenolic compounds
Bleaching	Unaffected